

RT- 3500

Vertical Microplate Washer

WHAT'S NEW

CENTRIFUGATION WASHER

4 PLATES SIMULTANEOUSLY

RESIDUAL VOLUME< 0.5µL



Features

- 8" LCD waterproof touch screen
- Optimal washing performance with centrifuge
- Wash up to 4 plates at a time
- 96-way manifold, automatic positioning
- Liquid level sensors with alert function for all bottles
- Extremely low residual volume < 0.5µL
- Automatic rinse to avoid liquid channels plugging
- O-rpm safety latch prevents the cover from opening by accident
- Linear speed control from 1500 to 2000 rpm
- Easy-to-use software requires minimal training for fast startup







Select plate/strip to wash

洗板	系统			维护			机	
演洗仓位及条数	126.1%							
F 00 00 1		0	6	4	6	6	7	8
60.60.2	1	2	3	4	(5)	6	7	(8)
10: 60: 3	1	2	(3)	4	(5)	6	7	(8)
10:102.4	1	2	(3)	4	(5)	6	7	(8)
200 H 100 H								
他がて	RIE (III	£3		洗泥	(美型	A液		
(I) sess		_	_	_	_	_	_	Rist

Washing program settings

默仏	21.00	清洗砂円(砂)	海洗水放	須窓町间(砂)	(R)水形间(19)
	1	2	5	10	15
	2				
	3				
	- 4				
	5				
	6				
	7				
	8				
上一	页	下一页			退出
D 88.4					

Easy maintenance

洗板 系统设置	维护	关机
日常清洗	化清洗	脱水
复位	灌注	排空
状态:日邓溥抚中,清朝被		



Technical Specifications

Plate Type	96-well plate or strip with flat/U/V-bottom
Plate Washing	1~4 plates programmable
Strip Washing	1~8 strips programmable
Wash Volume	flow rate 200~400 μL/s/well
	wash time and cycle adjustable
Wash Cycles	0~9 cycles
Memory	99 wash protocols
Wash Time	0~60.0s, step by 0.1s
Soak Time	0~999.9s, step by 0.1s
Spin Time	10~60.0s, step by 0.1s
Bottles	3 x 4L wash bottles
	1 x 4L rinse bottle
	1 x 10L waste bottle
Spin Speed	1500-2000 rpm adjustable
	step by 1 rpm, accuracy ±10%
Noise Level	≤70dB at maximum speed
Power Supply	AC 100~240 V, 50/60 Hz
Dimension(mm)	498 (L) x389 (W) x386 (H)
Weight	23 kg

Rayto Life and Analytical Sciences Co., Ltd.

Rayto Industrial Building, Shuangming Blvd South, East Hi-Tech Park, Guangming New District, 518107 Shenzhen, P.R.China. Tel: +86 (755) 88832350 Fax: +86 (755) 86168796

Email: info@rayto.com Web: www.rayto.com

